

Zeitschrift: IABSE congress report = Rapport du congrès AIPC = IVBH
Kongressbericht

Band: 12 (1984)

Artikel: Distribution of wheel loads on highway bridges

Autor: Sanders, Wallace W.

DOI: <https://doi.org/10.5169/seals-12236>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Siehe Rechtliche Hinweise.

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. Voir Informations légales.

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. See Legal notice.

Download PDF: 15.03.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Distribution of Wheel Loads on Highway Bridges

Wallace W. SANDERS, Jr.

Prof. Dr.

Iowa State University

Ames, IA, USA

The current criteria for the distribution of wheel loads in the U.S. bridge specifications have been undergoing change and expansion for over 50 years. The changes have primarily been introduced as modifications for a specific bridge type or condition with variations in the factors considered. As a result, the approach to the criteria has varied and resulted in inconsistencies in the codes. There now is a need for a complete review of load distribution in bridges recognizing a consistent approach to all bridge types and the availability of high speed computation.

There are a number of methods of analysis that can be used to develop load distribution behavior. These methods include: orthotropic plate, finite element or strip, grillage analogy, folded plate, influence surfaces. Using the selected methods, the effects of aspect ratio, bridge stiffness parameter, edge effects, load position, skew, continuity and diaphragms need to be evaluated for the broad types of bridges.

This study is needed and should result in a consistent criteria format based on similar parameters. It should consider all factors which affect behavior. The option should be available and encouraged to use one of the theories for complex structures, while providing a simple format for simple bridges.

DISTRIBUTION OF WHEEL LOADS ON HIGHWAY BRIDGES

Abstract

The current criteria for the distribution of wheel loads in U.S. bridge specifications have been undergoing changes over the last 20 years. These changes have been primarily introduced as modifications for a specific type of bridge or traffic load. As a result, the approach to the criteria has varied and the criteria have become increasingly complex. It is felt that a need for a complete review of load distribution in bridges exists and a more general approach to all bridge types and the availability of high-speed computers.



Method of Analysis

1. Orthotropic plate
2. Finite element or strip
3. Grillage analogy
4. Folded plate
5. Influence surfaces

Design Criteria



STANDARD SPECIFICATIONS
HIGHWAY BRIDGES



The American Association of State Highway
and Transportation Officials

DRIVEN — DESIGN
TEST — CERTIFY



HDR-44-A 8,000 lbs. 32,000 lbs. 32,000 lbs.

2 14' 2 14'

Percentage of Live Loads:
One lane 100%
Three lanes 90%
Four lanes or more 75%

Traffic Lane: 12' R. wide lanes (with 12' R. wide
shoulder) 10' C. shoulder. Lanes to be placed in
numbers and position to maximize effect.

Interior Beams: Wheel Load Fraction (typical)		
Kind of Floor	Bridge Designed for Single Traffic Lane	Bridge Designed for Double Traffic Lanes
Timber:		
E-Glued Laminated Panels on Glued Lam. Stringers	5.6.0	5.5.0
Concrete:		
Steel Beam Stringers or FC Girder	5.7.0	5.5.5
Concrete Box Girders	5.6.0	5.7.0

Exterior Beams:

a. Single beam reaction, or

b. Double beam reaction, or

c. 4 steel stringers, S = 14'

Special:
Steel Box Girders: Interior Load Fraction $\frac{25}{R_1}$, $\frac{25}{R_2}$
Composite Box Girders: Load Fraction $\frac{0.1 - 1.7R}{R_1}$, $\frac{0.1 - 1.7R}{R_2}$

Factors Affecting Design

1. Aspect ratio
2. Bridge stiffness parameter
3. Edge effects
4. Load position
5. Skew
6. Continuity
7. Diaphragms (type, location)

Specification Problems

1. Criteria format not consistent
2. Basis for criteria varies
3. Critical factors not considered
4. New bridge types require special studies
5. Loading conditions changed
6. Inconsistent safety factors
7. No criteria for rating

Current Design Practice

1. Timber deck/timber stringers
2. Concrete deck/steel I-beams
3. Concrete deck/P.C. girders
4. Steel grid decks/any stringer
5. Concrete deck/concrete T-beams
6. Segmental box girders
7. Concrete deck/spread box beams

Future Criteria

1. Load distribution criteria centralized
2. Simple criteria for "simple" bridges; Complex theories for "complex" bridges encouraged
3. Adaptable to all types of bridges
4. Separate design and rating criteria
5. Complete criteria for moment and shear

Produced by Office of Federal-aid
Highway Administration, April 1974