

Zeitschrift: IABSE congress report = Rapport du congrès AIPC = IVBH
Kongressbericht

Band: 12 (1984)

Artikel: Bridge strengthening by post-tensioning

Autor: Klaiber, F. Wayne / Sanders, Wallace W.Jr.

DOI: <https://doi.org/10.5169/seals-12255>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. [Siehe Rechtliche Hinweise.](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. [Voir Informations légales.](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. [See Legal notice.](#)

Download PDF: 15.03.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Bridge Strengthening by Post-Tensioning

F. Wayne KLAIBER

Prof. of Civil Engineering
Iowa State Univ.
Ames, IA, USA

Wallace W. SANDERS, Jr.

Prof. of Civil Engineering
Iowa State Univ.
Ames, IA, USA


During the period between 1940 and 1960, a number of single span steel beam composite concrete deck highway bridges were constructed in Iowa and throughout the United States. Design criteria at that time resulted in most of the exterior beams of these bridges being significantly smaller than the interior beams. As a result of changes in design standards and increases in legal load limits, many of these bridges cannot be rated for legal loads due to the capacity of their exterior beams. Rather than posting or replacing the bridges, a more attractive and economical alternative is to strengthen them. With research grants from the Iowa Department of Transportation and the Iowa Highway Research Board, a method of strengthening these bridges by post-tensioning has been developed. This study was divided into three phases. Phase I involved the development of bracket designs and the post-tension strengthening and testing of a half-scale model bridge in the laboratory. Phase II - the majority of which was completed during the summer of 1982 - involved the strengthening and testing (before and after strengthening) of two actual bridges. The final phase of the study (Phase III) involves the periodic inspection of the two bridges, their retesting during the summer of 1984, and the development of a practical design methodology for the strengthening technique. The major finding of Phases I and II was that post-tensioning is an economical and viable strengthening method. As may be noted in the graphs, there was considerable end restraint in both bridges (Bridge No. 1 and Bridge No. 2). Thus the post-tensioning was more effective in the laboratory models than on the actual bridges (due to the fact that there was no end-restraint). The end restraint on Bridges No. 1 and 2, however, also reduced the live load stresses. Thus in effect the end restraint effect on live load stresses and post-tensioning stresses compensate each other. Phase III of the study has been completed and the final report is presently being prepared. Both bridges previously strengthened were retested. Very little change was noted in their behavior from that noted during their initial strengthening two years earlier. The retesting made possible the determination of loss of prestress in both bridges; Bridges No. 1 and No. 2 had losses of approximately 5% and 7% respectively. This loss is primarily due to relaxation of the end restraint previously noted. Through the use of orthotropic plate theory and finite element models, a practical design methodology for determining the required post-tensioning forces has been developed for the design engineer and is included in the final report being prepared.

BRIDGE STRENGTHENING BY POST-TENSIONING

Abstract

During the period between 1940 and 1960, a number of single span steel beam composite concrete deck highway bridges were constructed in Texas and throughout the United States. Design criteria at that time resulted in most of the exterior beams of these bridges being significantly smaller than the interior beams. As a result of changes in design standards and increases in legal load limits, many of these bridges cannot be rated for legal loads due to the capacity of their exterior beams. Rather than posting or replacing the bridges, a more attractive and economical alternative is to strengthen them by post-tensioning.


Plexiglas Laboratory Model
1/4 Scale




Half Scale Bridge Model
26'-0" x 31'-10 1/2"




Bridge #1 Right Angle
51'-3" x 31'-10 1/2"




Bridge #2 45° Skew
71'-3" x 31'-10 1/2"




Arrangements of Post-Tensioning
Tendons and Bracket Detail Used on Bridge #1




Tendon Arrangement and
Bracket Detail Utilized on Bridge #2



Tendon Arrangement and
Bracket Detail Utilized on Bridge #1




Arrangement of Post-Tensioning
Tendons and Bracket Detail Used on Bridge #2



Results


Bottom Flange End Strains
Resulting From Post-Tensioning




Mid-Span Bottom Flange Strains
Resulting From Post-Tensioning




Moment Fractions
Resulting From Post-Tensioning



High Strength
Ball Shear Connectors



Comparison of Load-Slip Curves for
High Strength Balls and Weld Studs



Research Sponsored By
Highway Division
Texas Department of Transportation
Austin, Texas 78702

Prepared by M. J. Griffin, Texas A&M University