

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 2 (1978)
Heft: C-4: Structures in the USSR

Artikel: Bridge over the Sura River in Penza
Autor: [s.n.]
DOI: <https://doi.org/10.5169/seals-15096>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 13.07.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



3. Bridge over the Sura River in Penza

Designer: Design Institute Giprotransmost

Contractor: A constructional organization Glavmostostroi

*Sphere of application: The bridge is meant to have 4 lanes
for vehicular traffic and pedestrians*

Full deck width: 19,5 m including 15 m-wide roadway

*Static system: multispan frame cantilever bridge;
2-hinged frames with inclined pillars.*

Spans 52.9 + 4 x 56 + 52.9 m

Longitudinal grades: vary from 0 to 4 per cent

Materials used per m² of bridge:

— concrete for superstructure: 0.60 m³

— concrete for piers: 0.82 m³

— steel: 145.5 kg

— high-strength steel: 20.5 kg

Traffic opened: in 1975

The superstructure is erected of precast prestressed 2-hinged frames (having epoxy adhesive joints) with inclined pillars of "running fallow-deer" type.

The rated spans of the river frames are 53.73 m, the bank ones 50.63 m, each cantilever being 8.71 m long. The cantilevers of the frame cap of the adjacent spans are linked at the ends by longitudinal hinges, so as to form a 6-span scheme.

The bridge cross-section consists of 3 box frames placed at the distance of 6.3 m from each other.

The frame caps and suspended elements are made of pre-stressed concrete with reinforcement placed in closed ducts. The inclined pillars of the frames are made of ordinary concrete 500.

The frame cap depth varies from 200 cm at pier locations to 140 cm in the span middle and to 110 cm at the ends of the cap cantilevers.

The frames were assembled of separate elements weighing up to 37 tons on travelling metal trusses.

The bridge approaches are made as embankments and viaducts. The river piers are of streamline conical shape. Their foundations are made of d = 60 cm tubular piles 12 m long.

The test results proved sufficient rigidity and strength of the construction.



Fig. 1 The general view of the bridge