

# Research Institute and Data Center FRZ, Leoben

Autor(en): **Deutschmann, G**

Objektyp: **Article**

Zeitschrift: **IABSE structures = Constructions AIPC = IVBH Bauwerke**

Band (Jahr): **4 (1980)**

Heft C-12: **Structures in Austria**

PDF erstellt am: **22.07.2024**

Persistenter Link: <https://doi.org/10.5169/seals-16520>

## **Nutzungsbedingungen**

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern. Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden. Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

## **Haftungsausschluss**

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.



#### 4. Research Institute and Data Center FRZ, Leoben

**Owner:** VOEST-Alpine AG, formerly Österreichische Alpine Montangesellschaft  
**Planning:** Team Arch. E. Huth and G. Domenig, Graz  
**Design:** VOEST-Alpine AG and Dipl. Ing. G. Deutschmann, Zeltweg  
 Dipl. Ing. Haller and Dipl. Ing. Wendl, Graz  
**Steel structures:** VOEST-Alpine AG, Zeltweg, and Waagner-Biro AG, Graz  
**Façades:** VOEST-Alpine AG, Main workshop Eisenerz.

##### Main dimensions and weights:

**Height of building:** 28.5 m  
**Dimensions of center building:** 11.5×11.5 plus 11 m cantilevers on each side  
**Dimensions of lower building wing:** 33.5×42.5 m  
**Built-up area:** approx. 1500 m<sup>2</sup>  
**Built-up space:** approx. 27 m<sup>3</sup>  
**Usable Area:** 7250 m<sup>2</sup>  
 of which 37% are taken up for office rooms  
 approx. 27% for workshops and laboratories  
 approx. 17% for car parking lots  
 approx. 11% for traffic areas  
 and approx. 8% for files, protection and side rooms.  
**Material to be excavated:** approx. 12.7 m<sup>3</sup>  
**Reinforced concrete:** approx. 1700 m<sup>3</sup>  
**Reinforcing steel:** approx. 223 Mg  
**Steel requirements for center and side building (lower wing):** approx. 460 Mg  
**Koraldur for outer façade:** approx. 150 Mg  
**Bearing floors of "ALPINE-Bohlen", that is, slabs made of "Hüprocrete Concrete" with Donawitz foamed slag used as aggregate.**

##### Description of static system and of design

The steel structure comprises two principal groups: The tower-like central building with 7 floors, and the lower bay buildings for lab and computer rooms arranged around the tower.

The center building consists of 7 floor frames of a basic dimension of 11.5×11.4 m, with 4 columns welded together crosswise—torsionfree, and connected to the welded frame wall rails. The columns are connected with high-tensile bolts.

Within this prism, 2 pairs of inner columns are arranged orthogonally centric on each floor. They form the corridor proper on each floor.

The roof structure rests, statically determined, on the 4 column heads of the center frame so that it is free to move horizontally in 2 directions. On this plane, a fixed bearing holds the roof structure. This structure forms a spatial frame (lattice girder) whose system is made up by a grid which protrudes 11 m on all four sides and supports at the same time the suspended floors of the office wing.

The building elements of the roof, the suspensions, the floor beams, the façade and the office wing systems are of IPE sections—combined with wide flat steels—and bolted together. The steel structure in the rooms is visible and without sheeting.

**Steel grade used:** St 37 T and St 52 T  
**Total steel weight:** approx. 390 Mg

The lower bay wing arranged around the center building (dimensions: 33.5×42.5 m, width 11 m and 15.5 m) has one floor. This bay wing is articulated to the 2 basement floors of reinforced concrete. The structure consists of a welded steel frame, composed of IPE sections. In one of the wings a craneway and a working platform have been provided.



This structure arranged around the center building is self-supporting and not connected to the center building. The construction is of bolted design.

Steel grade used: St 37 T

Total steel weight: approx. 70 Mg

Calculation of the statically undetermined systems was made by a computer.

The outer facing was made of stain-resisting Koraldur steel plates and pipes.

Total weight of façade: approx. 150 Mg

The ground breaking was in October 1970, and the construction period lasted for three years.

(G. Deutschmann)

