

Zeitschrift: Helvetica Physica Acta
Band: 62 (1989)
Heft: 6-7

Artikel: Current voltage characteristics of semiconductor heterostructures : integration of sharply peaked transmissivities
Autor: Schlup, W.A. / Guéret, P.
DOI: <https://doi.org/10.5169/seals-116084>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. [Siehe Rechtliche Hinweise.](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. [Voir Informations légales.](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. [See Legal notice.](#)

Download PDF: 16.05.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

CURRENT VOLTAGE CHARACTERISTICS OF SEMICONDUCTOR HETEROSTRUCTURES — INTEGRATION OF SHARPLY PEAKED TRANSMISSIVITIES

W. A. Schlup and P. Guéret, IBM Research Division, Zurich Research Laboratory, CH-8803 Rüschlikon, Switzerland

Abstract: We investigate the current through a multibarrier/quantum well heterostructure assuming conservation of energy and of the momentum parallel to the interfaces. This current is given by the Esaki integral over the transmissivity $T(E, V_a)$. Energies with $T(E, 0) = 1$ correspond to the eigenvalues of the structure. For an applied voltage V_a the maxima give the resonances of the structure, whose widths are a measure for the tunneling probability through the corresponding barriers. If these probabilities are small, then the resonance lines become extremely narrow. If the precision of the computation is only a few orders of magnitude smaller, the results are very sensitive to the integration method especially near the first maximum of the $J(V_a)$ characteristic. Here we consider an extension of the trapezoidal method, which includes an exponential grid pattern near the resonances, taking into account the strong variation of $T(E, V_a)$. A few examples of simple heterostructure characteristics will be discussed.

Tunneling in heterostructures [1] consisting of AlGaAs barriers (width b_1, b_2 ; height V_1, V_2) separated by a well of GaAs (width b_{12} ; height $V_{12} = 0$) is the subject of intensive investigation. In the present work current-voltage characteristics derived from a simplified theory (ideal interfaces, no lateral inhomogeneities, no coherence-destroying effects such as inelastic scattering) resulting in the Esaki formula [2] are evaluated numerically. Comparison with the systematic experimental study by Guéret *et al.* will be published elsewhere [3],[4].

Consider independent quasifree electrons moving in an electric field V_a/L_a (L_a is the total length of the junction with a voltage V_a applied). Summed over the transverse k -vectors, the total current density as an integral over the longitudinal energies becomes

$$J(V_a) = \frac{em_t\theta}{2\pi\hbar^3} \int dE T(E, V_a) \ln \frac{1 + \exp(E_F - E)/\theta}{1 + \exp(E_F - E - V_a)/\theta}$$

where applied voltage V_a and temperature $\theta = k_B T_K$ are measured in energy units (eV). $T(E, V_a)$ is the transmissivity of the structure, i.e. the portion of electrons transmitted, which together with the reflectivity R adds up to $T + R = 1$. T can be found by the exact Airy-function [5] solution, whose coefficients related through four transfer matrices define T . Because of the lack of polynomial representations of Ai and Bi a plane wave approximation in subslices of width w ($w \sim 10 \text{ \AA}$) is used here, assuming a constant potential in each subslice.

For our typical symmetric double barrier junctions $b_1 = b_2 = 275 \text{ \AA}$, $V_1 = V_2 = 0.12 \text{ eV}$, $b_{12} = 70 \text{ \AA}$, $E_F = 0.012 \text{ eV}$ and $T_K = 4.2^\circ$, the transmissivity exhibits resonance peaks at energies $E_r(V_a)$, which for small V_a are narrow and well separated. The shape is Gaussian for $|E - E_r| \leq \Delta E_r^l$ and like $1/(E - E_r)^2$ (Lorentzian) for $|E - E_r| \gg \Delta E_r^l$ (ΔE_r^l is the halfwidth of the r -th resonance) as long as the next resonance is not interfering. With increasing V_a , resonances shift towards smaller energies $E_r(V_a) = E_{r0} - 0.5V_a + O(V_a^2)$ and increase in width according to $\Delta E_r^l(V_a) = \Delta E_{r0}^l(1 + C_r V_a^2 + \dots)$; values for the above parameters are $\Delta E_{10}^l = 5.2 \times 10^{-11} \text{ eV}$, ($C_1 = 850$), $\Delta E_{20}^l = 1.7 \times 10^{-4}$, etc. Because of the extremely small width of the first resonance, which contributes mainly to the first maximum in the $J(V_a)$ characteristic, a special integration method has been developed. It is an extension of the trapezoidal method [6] by means of linearly distributed grid points with grid interval δE including an r -dependent exponential grid near resonance energies according to $E_{r\lambda}^\pm = E_r(V_a) \pm \delta E_r p_r^\lambda$ with $r = 1, 2, \dots$, $\lambda = 0, 1, \dots, \Lambda_r$, where Λ_r is chosen such that $\delta E_r p_r^{\Lambda_r} \cong \Delta E_r^l$; because of the exponential decay of the peak, $p_r \cong 1/2$ and $\delta E_r \cong \delta E$ give best results. The precision has been checked by halving the grid steps, which are typically 10^{-3} for our example. Characteristics thus derived are reliable if the subslice width is $w = 5 \text{ \AA}$ if the applied voltages are not too large $|V_a| < 0.2 \text{ eV}$.

In contrast to adaptive integration methods [6] our method avoids IF commands and is hence more appropriate for vector processor computing.

The authors acknowledge valuable discussions with A. Baratoff.

References

- [1] C.B. Duke, *Tunneling in Solids* (Academic Press, New York, 1969) Chapt. IV.7.
- [2] R. Tsu and L. Esaki, *Appl. Phys. Lett.* **22**, 562 (1973).
- [3] P. Guéret, C. Rossel, E. Marclay and H. Meier, *J. Appl. Phys.* **65**, 4999 (1989).
- [4] P. Guéret, C. Rossel, W.A. Schlup and H. Meier (to be published).
- [5] M. Abramowitz and I.A. Stegun, *Handbook of Mathematical Functions* (Dover Publications, New York, 1965).
- [6] H.R. Schwarz, *Numerische Mathematik* (Teubner, Stuttgart, 1988) Chapt. 8.